

# **SPECIFICATIONS**

<b>Model</b>	<b>1111</b>	<b>1311</b>
Capacity*	1,100 bu.	1,300 bu.
Undercarriage tire size	Single 1050/50x32	Single 76/50x32
Unloading time	800 bu./min.	800 bu./min.
Hitch, standard	Single tang	Single tang
Approx. empty weight	15,550 lbs.	18,475 lbs.
Est. loaded tongue weight	5,200 lbs.	5,375 lbs.
Vertical auger size	22"	22"
Horizontal auger size	20"	20"
Spindle diameter	<u>4½" single</u> 3¾" duals	<u>5½" single</u> 3¾" duals
PTO yoke, standard	1-3/4" x 20 spline	1-3/4" x 20 spline
Overall width	12'	12'
Overall length	30' 10"	30' 10"
Overall height	12' 2"	12' 8"
Height loading side	10' 10"	11' 4"
Auger unloading height	14' 4"	14' 4"
Auger reach	7'	7'

\*Capacities measured with #2 corn @ 15% moisture (56 lb. test weight)

# **TRACK SYSTEM SPECIFICATIONS**

<b>Model</b>	<b>1111</b>	<b>1311</b>
Bogie wheels	8	16
Belt width	36"	36"
Belt length	130"	148"
Ground contact length	90"	105"
Ground contact area (square inches)	3,240	3,780

# **LOADED CART GROUND PRESSURE**

<b>Model</b>	<b>1111</b>	<b>1311</b>
Tracks	12.66	13.29
520/85x38 duals	19.8	—
520/85x42 duals	18.78	24.06
650x65x42 duals	17.06	22.34
76-50.00x32	17.86	22.01
1050/50x32	21.28	—

Due to continuing improvements in the design and manufacture of Unverferth products, all specifications contained herein are subject to change without notice.