

Specifications

Models 875, 1075, 1280 & 1396

	875 8-ton	1075 10-ton
Spindle diameter	1 3/4"	2"
Tapered roller bearing	inner 1.5" outer 1.25"	inner 1.625" outer 1.250"
Axles, channel	6" x 2" x 5/16"	6" x 2" x 5/16"
Hub bolts (#)	6	6
Standards	38" or 42"	38" or 42"
Tongue -Adjustable quick-hitch	73"-103"	73"-103"
Wagon weight, less tires	660 lbs.	730 lbs.
Wheelbase	84"-132"	84"-132"
Ground Clearance (Tire Dependent)	13"	13"

Model	1280 12-ton	1396 13-ton
Spindle diameter	2 1/4"	2 1/2"
Tapered roller bearing	inner 1.781" outer 1.25"	inner 1.625" outer 1.250"
Axles, rectangular tube	6" x 3" x 1/4"	6" x 3" x 1/4"
Hub bolts (#)	8	8
Standards	38" or 42"	38" or 42"
Tongue - Adjustable quick-hitch	73"-103"	75"-105"
Brake Option (2 surge brakes)	NA	Yes
Wagon weight, less tires	952 lbs.	1490 lbs.
Wheelbase	108"-132"	96"-144"
Ground Clearance (Tire Dependent)	18"	12"

Unverferth Manufacturing reserves the right to make changes in engineering, design and specifications at any time without notice or obligation.